


**Document of Performance  
According to Regulation (EU) 305/2011**

Aduro 13, Aduro 13-1		PoD No: 13 0004
Roomheater burning solid fuel <u>without</u> hot water supply. EN 13240:2001/A2:2004/AC:2007		
Aduro AS, Beringvej 17, DK-8361 Hasselager, Denmark. <a href="http://www.aduro.dk">www.aduro.dk</a> , <a href="mailto:info@aduro.dk">info@aduro.dk</a> , Tel.: +45 70274703.		
System 3 of assessment and verification of constancy of performance of the construction product: Internal quality security system in combination with external production control.		
Rhein-Ruhr Feuerstätten Prüfstelle GmbH, Im Lipperfeld 34 b, D-46047 Oberhausen, notified body number: 1625 and Teknologisk Institut, Kongsvang 29, DK-8000 Aarhus, notified body number: 300.		
performed the determination of the product type on the basis of type testing under system 3 and <u>issued test report</u> : RRF- 40 12 3153 300-ELAB-1650-NS		
Declared performance		
<b>Harmonized technical specification</b>	EN 13240:2001/A2:2004/AC:2007	
<b>Essential characteristics</b>	<b>Performance</b>	
<b>Fire safety</b>		
Reaction to fire	A1	
Distance to combustible materials Distance marked with * is for installation with isolated pipe	Minimum distances, in mm rear = 210/*90 sides = 460 front = 1000	
Risk of burning fuel falling out	Pass	
<b>Emission of combustion products</b>	CO[0.09 %]	
<b>Surface temperature</b>	Pass	
<b>Electrical safety</b>	NPD	
<b>Cleanability</b>	Pass	
<b>Maximum water operating pressure</b>	NPD	
<b>Flue gas temperature at nominal heat output</b>	T [283 °C]	
<b>Mechanical resistance (to carry a chimney/flue)</b>	NPD	
<b>Thermal output</b>		
Nominal heat output	5 kW	
Room heating output	5 kW	
Water heating output	"" kW	
<b>Energy efficiency</b>	$\eta$ [80,5 %]	

Signed for and on behalf of the manufacturer by:

Christian Skovbo, CEO, Aduro AS  
Hasselager, 24-06-2013

 **Aduro A/S**  
Beringvej 17  
DK-8361 Hasselager  
Tel.: +45 70274703  
Fax: +45 70274704  
CVR-nr.: 28488602