

**Document of Performance
According to Regulation (EU) 305/2011**

| | | |
|---|--|-----------------|
| Aduro 15, Aduro 15SK, Aduro 15.1, Aduro 15.2, Aduro 15.3, Aduro 15.4 | | DoP No: 15 0001 |
| Roomheater burning solid fuel without hot water supply. | | |
| EN 13240:2001/A2:2004/AC:2007 | | |
| Aduro AS, Beringvej 17, DK-8361 Hasselager, Denmark. www.aduro.dk , info@aduro.dk , Tel.: +45 70274703. | | |
| System 3 of assessment and verification of constancy of performance of the construction product: Internal quality security system in combination with external production control. | | |
| Rhein-Ruhr Feuerstätten Prüfstelle GmbH, Im Lipperfeld 34 b, D-46047 Oberhausen, notified body number: 1625 and Teknologisk Institut, Kongsvang 29, DK-8000 Aarhus, notified body number: 300. | | |
| performed the determination of the product type on the basis of type testing under system 3 and issued test report: RRF- 40 14 3560 / RRF 40 15 4038/ RRF 40 16 4334 300-ELAB-2060-NS | | |
| Declared performance | | |
| Harmonized technical specification | EN 13240:2001/A2:2004/AC:2007 | |
| Essential characteristics | Performance | |
| Fire safety | | |
| Reaction to fire | A1 | |
| Distance to combustible materials Distance marked with * is for installation with isolated pipe | Minimum distances, in mm rear = 200/*120 sides = 340 front = 1200 | |
| Risk of burning fuel falling out | Pass | |
| Emission of combustion products | CO[0,1 %] | |
| Surface temperature | Pass | |
| Electrical safety | NPD | |
| Cleanability | Pass | |
| Maximum water operating pressure | NPD | |
| Flue gas temperature at nominal heat output | T [329 °C] | |
| Mechanical resistance (to carry a chimney/flue) | NPD | |
| Thermal output | | |
| Nominal heat output | 6,5kW | |
| Room heating output | 6,5 kW | |
| Water heating output | *** kW | |
| Energy efficiency | η [78 %] | |

Signed for and on behalf of the manufacturer by:

Christian Skovbo, CEO, Aduro AS
Hasselager, 05.01.2022

