



**Document of Performance
According to Regulation (EU) 305/2011**

Aduro 7-1, Aduro 7-2	DoP No: 7-1 0001
Roomheater burning solid fuel <u>without</u> hot water supply.	
EN 13240:2001/A2:2004/AC:2007	
Aduro AS, Beringvej 17, DK-8361 Hasselager, Denmark. www.aduro.dk , info@aduro.dk , Tel.: +45 70274703.	
System 3 of assessment and verification of constancy of performance of the construction product: Internal quality security system in combination with external production control.	
Teknologisk Institut, Kongsvang 29, DK-8000 Aarhus, notified body number: 300.	
performed the determination of the product type on the basis of type testing under system 3 and <u>issued test report</u> :	
300-ELAB-2098-NS, 300-ELAB-2098 EN	

Declared performance

Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials Distance marked with * is for installation with isolated pipe	Minimum distances, in mm rear = 250 sides = 700 (145 mm Behind the stove : 500) front = 1025
Risk of burning fuel falling out	Pass
Emission of combustion products	CO[0.08 %]
Surface temperature	Pass
Electrical safety	NPD
Cleanability	Pass
Maximum water operating pressure	NPD
Flue gas temperature at nominal heat output	T [295°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Nominal heat output	7,0 kW
Room heating output	7,0 kW
Water heating output	"" kW
Energy efficiency	η [78 %]

Signed for and on behalf of the manufacturer by:

Christian Skovbo, CEO, Aduro AS
Hasselager, 29.04-2016

.....