



**Document of Performance
According to Regulation (EU) 305/2011**

Aduro P4 Series		DoP No: P4 0001
Residential space heating appliance fired by wood pellets without hot water supply. EN 14785: 2008; CEN/TS 15883:2009		
Aduro AS, Beringvej 17, DK-8361 Hasselager, Denmark. www.aduro.dk , info@aduro.dk , Tel.: +45 70274703.		
System 3 of assessment and verification of constancy of performance of the construction product: Internal quality security system in combination with external production control.		
SZU, Hudcova 424/56b, 621 00 Brno, notified body number: 1015. performed the determination of the product type on the basis of type testing under system 3 and <u>issued test report</u> : 30-15199/3/T		
Declared performance		
Harmonized technical specification	EN 14785:2008; CEN/TS 15883:2009	
Essential characteristics	Performance	
Fire safety		
Reaction to fire	A1	
Distance to combustible materials Distance marked with * is for installation with isolated pipe	Minimum distances, in mm rear = 100 sides = 100 front = 800	
Risk of burning fuel falling out	Pass	
Emission of combustion products Pellets Nominal Heat	CO [0.02 %]	
Emission of combustion products Pellets Reduced Heat	CO [0.02 %]	
Surface temperature	Pass	
Electrical safety	Pass	
Cleanability	Pass	
Maximum water operating pressure	NPD	
Flue gas temperature at nominal heat output	T [118°C]	
Mechanical resistance (to carry a chimney/flue)	NPD	
Thermal output		
Nominal heat output Pellets	8,0 kW	
Room heating output	8,0 kW	
Water heating output	... kW	
Energy efficiency Pellets	η [>90 % by Nominal output] η [>92 % by Reduced output]	

Signed for and on behalf of the manufacturer by:

Christian Skovbo, CEO, Aduro AS
Hasselager, 23.12.2021