

**Document of Performance
According to Regulation (EU) 305/2011**

| | | |
|---|---|-----------------|
| Aduro 20 Series | | DoP No: 20 0001 |
| Roomheater burning solid fuel <u>without</u> hot water supply. EN 13240:2001/A2:2004/AC:2007 | | |
| Aduro AS, Beringvej 17, DK-8361 Hasselager, Denmark. www.aduro.dk , info@aduro.dk , Tel.: +45 70274703. | | |
| System 3 of assessment and verification of constancy of performance of the construction product: Internal quality security system in combination with external production control. | | |
| Rhein-Ruhr Feuerstätten Prüfstelle GmbH, Im Lipperfeld 34 b, D-46047 Oberhausen, notified body number: 1625 and Teknologisk Institut, Kongsvang 29, DK-8000 Aarhus, notified body number: 300. | | |
| performed the determination of the product type on the basis of type testing under system 3 and <u>issued test report</u> | | |
| RRF –ITT 18 4917 300-ELAB-2060-NS | | |
| Declared performance | | |
| Harmonized technical specification | EN 13240:2001/A2:2004/AC:2007 | |
| Essential characteristics | Performance | |
| Fire safety | | |
| Reaction to fire | A1 | |
| Distance to combustible materials Distance marked with * is for installation with isolated pipe | Minimum distances, in mm rear = 200/ 120* sides = 340/ 110 front =1200 | |
| Risk of burning fuel falling out | Pass | |
| Emission of combustion products Wood | CO[0.07 %] | |
| Surface temperature | Pass | |
| Electrical safety | NPD | |
| Cleanability | Pass | |
| Maximum water operating pressure | NPD | |
| Flue gas temperature at nominal heat output Wood | T [329°C] | |
| Mechanical resistance (to carry a chimney/flue) | NPD | |
| Thermal output | | |
| Nominal heat output Wood | 6,5 kW | |
| Room heating output | 6,5 kW | |
| Water heating output | *** kW | |
| Energy efficiency Wood | η [78 %] | |

Signed for and on behalf of the manufacturer by:

Christian Skovbo, CEO, Aduro AS
Hasselager, 30-06-2018



.....